



GO

Celerway GO is the only portable, battery-powered mobile router to deliver Gigabit class connectivity with VPN encryption virtually anywhere, while being small enough to fit in your hand or stow in a laptop case.

Thanks to its innovative use of 2 simultaneous cellular WAN connections, GO gives teams working remotely—whether at stationary remote locations or on the go—seamless, secure access to company resources and IT infrastructure as if they'd never left the office.

Maximum load balancing capacity	950 Mbps
Phantom VPN encryption	180 Mbps
IPSec VPN encryption	60 Mbps
Maximum number of simultaneous WANs	5
Dimensions w x h x d	79 mm x 141 mm x 30 mm
Weight	0.33 kg
Operating temperature	5 °C to 35 °C
Humidity	5% to 85%
Power supply	USB-C 5V, 3A
Power consumption	8-20W depending on use
Integrated cellular	1 x CAT12 or 2 x CAT12 depending on model
Region	Global
SIM card slot	2 x Micro
eSIM support	eUICC with 3FF/4FF
Ethernet (WAN and/or LAN)	2 x 10/100/1000 Mbps RJ-45
Wi-Fi (WAN and/or LAN)	2.4GHz + 5GHz simultaneous dual-band
USB	2 x USB-C (self-charging, other device charging)
Mini-PCIe	-
M.2	1 x or 2 x depending on model
Antenna connectors cellular	2 x SMA female
Antenna connectors WiFi	-
Antenna connectors GPS	-

Battery power rating 10000mAh

Operating time 7 hours

US carrier-ready AT&T, FirstNet, Verizon, T-Mobile

GO Double modem

3YP-CWY-M5.1-E2L2W2B

EAN 7090049150388

THEORETICAL DOWNLOAD RATES

THEORETEICAL UPLOAD RATES

Region	Global + Global
Dual SIM	Yes + Yes
Theoretical Upload Rate	150 Mbps + 150 Mbps
Theoretical Download Rate	600 Mbps + 600 Mbps
LTE-FDD	B1/B2/B3/B4/B5/B7/B8/B9/ B12/B13/B14/B17/B18/B19/ B20/B21/B25/B26/B28/B29/B30/B32/B66 + B1/B2/B3/B4/B5/B7/B8/B9/ B12/B13/B14/B17/B18/B19/ B20/B21/B25/B26/B28/B29/B30/B32/B66
LTE-TDD	B38/39/B40/B41 + B38/39/B40/B41
WCDMA	B1/B2/B3/B4/B5/B8/B19 + B1/B2/B3/B4/B5/B8/B19
2xCA	B1+3/5/18/19/20/26; B2+2/4/5/12/13/17/29/30/66; B3+3/5/7/8/19/20/28; B4+4(CA_4C only)/5/12/13/17/29/30; B5+7/25/30/66; B7+7/20/28; B12+25; B12+30; B13+66; B19+21; B20+B32; B25+25; B25+26; B25+41; B29+30; B38+38(CA_38C only); B40+B40; B41+B41; B66+B66; + B1+3/5/18/19/20/26; B2+2/4/5/12/13/17/29/30/66; B3+3/5/7/8/19/20/28; B4+4(CA_4C only)/5/12/13/17/29/30; B5+7/25/30/66; B7+7/20/28; B12+25; B12+30; B13+66; B19+21; B20+B32; B25+25; B25+26; B25+41; B29+30; B38+38(CA_38C only); B40+B40; B41+B41; B66+B66;

3xCA DL interband 3CA:

B1+3+5/7/8/19/20/28; B1+7+20;
B2+4+5; B2+4+13; B2+5+30; B2+12+30; B2+29+30;
B3+7+20; B3+7+28; B3+7+8;
B4+5+30; B4+12+30; B4+29+30; B5+66+2; B13+66+2;
B66+12+30; B66+29+30; B66+5+30; B2+B14+B66;

DL2 intraband plus interband 3CA:

B2+2+5; B2+2+13; B3+3+7; B3+7+7; B3+3+20;
B3+3+28; B3+3+1; B4+4+5; B4+4+13;
B7+7+28; B5+66+66; B13+66+66;
B66+66+2; B39+B39+B41; B39+B41+B41;
B14+B66+B66;

DL3 intraband 3CA:

B40+40+40; B41+41+41; B66+66+66;
+

DL interband 3CA:

B1+3+5/7/8/19/20/28; B1+7+20;
B2+4+5; B2+4+13; B2+5+30; B2+12+30; B2+29+30;
B3+7+20; B3+7+28; B3+7+8;
B4+5+30; B4+12+30; B4+29+30; B5+66+2; B13+66+2;
B66+12+30; B66+29+30; B66+5+30; B2+B14+B66;

DL2 intraband plus interband 3CA:

B2+2+5; B2+2+13; B3+3+7; B3+7+7; B3+3+20;
B3+3+28; B3+3+1; B4+4+5; B4+4+13;
B7+7+28; B5+66+66; B13+66+66;
B66+66+2; B39+B39+B41; B39+B41+B41;
B14+B66+B66;

DL3 intraband 3CA:

B40+40+40; B41+41+41; B66+66+66;

WiFi Theoretical Data Rate 300Mbps + 867Mbps

WiFi Protocol b/g/n + a/ac/b/g/n

WiFi Frequency 2.4GHz + 5GHz

Last modified 23-May-2022 20:33:23



At Celerway, we're on a mission
to keep business ahead of the
mobile curve.

© 2022 Celerway Communication AS
Lilleakerveien 2B, 0283 Oslo, Norway
+47 45 50 71 02 info@celerway.com

THEORETICAL DOWNLOAD RATES

THEORETEICAL UPLOAD RATES

Region	Global
Dual SIM	Yes
Theoretical Upload Rate	150 Mbps
Theoretical Download Rate	600 Mbps
LTE-FDD	B1/B2/B3/B4/B5/B7/B8/B9/ B12/B13/B14/B17/B18/B19/ B20/B21/B25/B26/B28/B29/B30/B32/B66
LTE-TDD	B38/39/B40/B41
WCDMA	B1/B2/B3/B4/B5/B8/B19
2xCA	B1+3/5/18/19/20/26; B2+2/4/5/12/13/17/29/30/66; B3+3/5/7/8/19/20/28; B4+4(CA_4C only)/5/12/13/17/29/30; B5+7/25/30/66; B7+7/20/28; B12+25; B12+30; B13+66; B19+21; B20+B32; B25+25; B25+26; B25+41; B29+30; B38+38(CA_38C only); B40+B40; B41+B41; B66+B66;
3xCA	DL interband 3CA: B1+3+5/7/8/19/20/28; B1+7+20; B2+4+5; B2+4+13; B2+5+30; B2+12+30; B2+29+30; B3+7+20; B3+7+28; B3+7+8; B4+5+30; B4+12+30; B4+29+30; B5+66+2; B13+66+2; B66+12+30; B66+29+30; B66+5+30; B2+B14+B66; DL2 intraband plus interband 3CA: B2+2+5; B2+2+13; B3+3+7; B3+7+7; B3+3+20; B3+3+28; B3+3+1; B4+4+5; B4+4+13; B7+7+28; B5+66+66; B13+66+66; B66+66+2; B39+B39+B41; B39+B41+B41; B14+B66+B66; DL3 intraband 3CA: B40+40+40; B41+41+41; B66+66+66;
WiFi Theoretical Data Rate	300Mbps + 867Mbps
WiFi Protocol	b/g/n + a/ac/b/g/n
WiFi Frequency	2.4GHz + 5GHz



At Celerway, we're on a mission
to keep business ahead of the
mobile curve.

© 2022 Celerway Communication AS
Lilleakerveien 2B, 0283 Oslo, Norway
+47 45 50 71 02 info@celerway.com